

# Technical data sheet

## Equipotential busbar for small systems

Item number: 5015502



- Cover made of polystyrene, grey
- Sealable/labellable
- Base plate made of strip galvanised steel
- Contact strip and screws made of nickel-plated brass

Connection options:

- 3 x multi-core cables to 6 mm<sup>2</sup>
- 2 x multi-core cables to 16 mm<sup>2</sup>



**CuZn**  
37 Brass

### Master data

Item number	5015502
Type	1809 BG
Description 1	Equipotential busbar
Description 2	for small systems
Manufacturer	OBO
Dimension	72x45mm
Colour	Grey
Material	Brass
Smallest sales unit	1
Unit of quantity	Piece
Weight	9 kg
Weight unit	kg/100 pc.


# Technical data sheet

## Equipotential busbar for small systems



Item number: 5015502

### Dimensions



Length	72 mm
Width	43.5 mm
Height	29 mm



### Technical data

Quantity of flat conductor connections up to 30 mm	0
Quantity of flat conductor connections up to 40 mm	0
Quantity of cable connections up to 16 mm <sup>2</sup> , rigid	2
Quantity of cable connections up to 25 mm <sup>2</sup> , rigid	0
Quantity of cable connections up to 6 mm <sup>2</sup> , rigid	3
Quantity of cable connections up to 95 mm <sup>2</sup> , rigid	0
Quantity of round conductor connections 10 mm	0
Quantity of round conductor connections 8 mm	0
Quantity of round conductor connections 8-10 mm	0
Quantity of round conductor connections, total	0
Version for	With cover hood
Type	Fixed structure
Insulator	no
Surface of the terminal	Nickel-plated
Surface of the contact rail	Nickel-plated
Material of the terminal	Brass
Material of the contact rail	Brass