


Technical data sheet

Dolü branch terminals, open on both sides, 12-pin

Item number: 2055023



Sorted in colours black, brown, blue and yellow-green.

Terminals made of brass, screws of steel, galvanised and transparently passivated, 12-pole, strip separable into individual terminals, open on both sides.

Captive upwards screw.

Nominal cross-section $2.5 \pm \text{mm}^2$.

Nominal voltage 380 V.

Nominal current 16 A.

Max. connectable cross-sections per terminal: $4 \times 2.5 \text{ mm}^2$, $5 \times 1.5 \text{ mm}^2$ or $6 \times 1 \text{ mm}^2$.

Delivery sorted by colour: 5 black, 2 blue, 2 yellow-green and 1 brown strip in each packaging unit.



PA Polyamide

Master data

Item number	2055023
Type	70 VDE
Description 1	Dolü branch terminal
Description 2	colours sorted
Manufacturer	OBO
Dimension	2,5mm ²
Colour	(sorted)
Material	Polyamide
Smallest sales unit	10
Unit of quantity	Piece
Weight	2.5 kg
Weight unit	kg/100 pc.


Technical data sheet

Dolü branch terminals, open on both sides, 12-pin

Item number: 2055023



Dimensions



Length	122 mm
Width	15 mm
Height	17 mm

Technical data

Closing plate required	no
Connectable conductor cross-section, single-wire, max.	2.5 mm ²
Connectable conductor cross-section, single-wire, min.	1 mm ²
Connection position	Side
No. of terminals	12
Number of screwless terminals per pole	1
Version of electrical connection 1	Screw connection
Drill hole spacing, centre	10.25 mm
Explosion-tested version	no
Suitable for flexible conductors	yes
Suitable for solid conductors	no
Suitable for multi-wire conductors	yes
Halogen-free	yes
Insulation material	Thermoplast
Mounting type	Direct mounting
Nominal cross-section, min.	2.5 mm ²
Nominal voltage	380 V
Nominal current	16 A
Pole number	12
Cross-section	Max. connectable cross-sections per terminal: 4 x 2.5 mm ² , 5 x 1.5 mm ² or 6 x 1 mm ² mm ²
Transparent	no