Technical data sheet Support bracket AS 15

Item number: 6421466



Light-duty support bracket for infinitely adjustable fastening on IS 8 support. The support bracket can be fastened to both sides of the I support.

The necessary clamping lug (item no. 6419015), including bolt and nut can be ordered individually for bracket widths 110–160 mm.





FT

Hot-dip galvanised


Master data

Item number6421466TypeAS 15 51 FTDescription 1Support bracketDescription 2for IS 8 supportManufacturerOBODimensionB510mmMaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1Unit of quantityPiece		
Description 1Support bracketDescription 2for IS 8 supportManufacturerOBODimensionB510mmMaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1	Item number	6421466
Description 2for IS 8 supportManufacturerOBODimensionB510mmMaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1	Туре	AS 15 51 FT
ManufacturerOBODimensionB510mmMaterialSteelSurfaceHot-dip galvanisedSurface standardDIN EN ISO 1461Smallest sales unit1	Description 1	Support bracket
Dimension B510mm Material Steel Surface Hot-dip galvanised Surface standard DIN EN ISO 1461 Smallest sales unit 1	Description 2	for IS 8 support
Material Steel Surface Hot-dip galvanised Surface standard DIN EN ISO 1461 Smallest sales unit 1	Manufacturer	OBO
Surface Hot-dip galvanised Surface standard DIN EN ISO 1461 Smallest sales unit 1	Dimension	B510mm
Surface standard DIN EN ISO 1461 Smallest sales unit 1	Material	Steel
Smallest sales unit 1	Surface	Hot-dip galvanised
	Surface standard	DIN EN ISO 1461
Unit of quantity Piece	Smallest sales unit	1
	Unit of quantity	Piece
Weight 79.6 kg	Weight	79.6 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet Support bracket AS 15

Item number: 6421466






Length	41 mm
Width	510 mm
Height	75 mm
Dimension A	41 mm
Dimension B	510 mm
Dimension H	75 mm


Technical data

Version for	Support bracket
EPD article	yes
F in kN	1.5 kN
Maintain electrical functions	no
Rustproof steel, pickled	no



Load diagram, bracket type AS 15

- Bending of the bracket tip at permitted bracket load
- 2 Permitted bracket load in kN without man load



Load curve with bracket lengths in mm