


Technical data sheet

External corner, symmetrical, for device installation trunking Rapid 80 type GA-S70170

Item number: 6279113



External corner for changing the direction of the Rapid 80 GA aluminium device installation trunking.
The visible surfaces of the fittings are laminated. The cover must be ordered separately.



Alu Aluminium

EL Anodised

Master data

| | |
|---------------------|-----------------|
| Item number | 6279113 |
| Type | GA-SA70170EL |
| Description 1 | External corner |
| Description 2 | symmetrical |
| Manufacturer | OBO |
| Dimension | 70x170x300 |
| Material | Aluminium |
| Surface | Anodised |
| Surface standard | |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 202.2 kg |
| Weight unit | kg/100 pc. |

Technical data sheet

External corner, symmetrical, for device installation trunking Rapid 80 type GA-S70170


Item number: 6279113



Dimensions



| | |
|--------|--------|
| Length | 300 mm |
| Width | 170 mm |
| Height | 70 mm |



Technical data

| | |
|-----------------------------------|----------|
| Number of covers | 1 |
| Version for | Base |
| for duct width | 170 mm |
| for trunking height | 70 mm |
| Halogen-free | yes |
| Cable retaining clip | no |
| Duct connector | no |
| Cover mounting type | Internal |
| Mounting perforation in base | no |
| Cover width | 76.5 mm |
| Protection rating | IP30 |
| Protective film | yes |
| Protection rating IK code | IK10 |
| Symmetrical | yes |
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -25 °C |
| Angle range, min. | 90 mm |