Technical data sheet

Service outlet with blanking cover and Allen slot, GES R2, nickel

Item number: 7408870



Service outlet with blanking cover and Allen slot for GES R2 floor socket for direct installation in the MT R2 installation socket in indoor areas.

The cover version can be used as a cable outlet.

When closed, the floor socket can be wet-cleaned.







Die-cast zinc



Nickel-plated

B.A		4-	_	_	4-
IVI	as	te	ш	а	ιa

Item number	7408870		
Type	GES R2B Ni		
Description 1	Floor socket		
Description 2	blind with Allen key recess		
Manufacturer	OBO		
Material	Die-cast zinc		
Surface	Nickel-plated		
Surface standard			
Smallest sales unit	1		
Unit of quantity	Piece		
Weight	58.32 kg		
Weight unit	kg/100 pc.		

Technical data sheet

Service outlet with blanking cover and Allen slot, GES R2, nickel





Technical data		
	Version for	Round
	Cable outlet version	No cable outlet
	Floor covering protection frame	yes
	Floor care	Wet
	Suitable for raised floor installation	yes
	Suitable for cavity floor installation	yes
	Suitable for wet care	yes
	Suitable for underfloor ducts	no
	With floor covering recess	no
	Standard	EN 50085-2-2
	Protection rating (IP) when unused	IP66
	Protection rating IK code	IK10
	Vertical load, large area	to 15,000 N
	Vertical load, small area	to 3,000 N
	Approvals	VDE
	Opening mechanism	Tool