Technical data sheet

Service pole, type ISS110100R

Item number: 6289060



ISS aluminium service pole with a thin tube to the ceiling.

Set consists of:

1 single-compartment pole with clamping fastening

Total length 3,315–3,480 mm

- 1 clamping device for clamping to the ceiling
- 1 equippable aluminium installation area

Length: 780 mm

In areas for device installation, the service pole has a 76.5 mm system opening and is suitable for accepting front-locking accessory mounting boxes of the series 71GD...



Master data

Item number		
Description 1 Service pole Description 2 floor/ceiling Manufacturer OBO Dimension 3000x100x110 Colour Pure white; RAL 9010 Material Aluminium Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Item number	6289060
Description 2 floor/ceiling Manufacturer OBO Dimension 3000x100x110 Colour Pure white; RAL 9010 Material Aluminium Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Туре	ISS110100RRW
Manufacturer OBO Dimension 3000x100x110 Colour Pure white; RAL 9010 Material Aluminium Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Description 1	Service pole
Dimension 3000x100x110 Colour Pure white; RAL 9010 Material Aluminium Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Description 2	floor/ceiling
Colour Pure white; RAL 9010 Material Aluminium Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Manufacturer	OBO
Material Aluminium Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Dimension	3000x100x110
Smallest sales unit 1 Unit of quantity Piece Weight 1000 kg	Colour	Pure white; RAL 9010
Unit of quantity Piece Weight 1000 kg	Material	Aluminium
Weight 1000 kg	Smallest sales unit	1
	Unit of quantity	Piece
Waight unit	Weight	1000 kg
weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet

Service pole, type ISS110100R





| Length | 3,000 mm | Width | 100 mm | Height | 110 mm |

Technical data

Number of usable covers	1
Number of compartments	1 St.
Version for	Single-sided
Fastening type	Tension
Floor mounting	yes
Ceiling mounting	yes
Continuous profile	no
Halogen-free	yes
Height compensation, max.	480 mm
Height compensation, min.	315 mm
Cable entry	Top/bottom
Cover width	76.5 mm
Changes according to location	no
Pole shape	Installation space, angular/pole, round
Pole height, max.	3480 mm
Pole height, min.	3315 mm
Adjustable	yes
Pre-wired	no