# Technical data sheet

Mounting support, 2 x type C

### Item number: 7407848



Mounting support to accept two data connection modules of the following types: Brand-Rex: shielded; EKU: E-Stone; Dätwyler: KS-T, MS-K and KU-T module; R&M: Snap-In and Keystone; Rutenbeck: UM and UMflex; SETEC: MKJ, UKJ and XKJ; Siemon TERA; Telegärtner: AMJ and UMJ.

Dimensions of a mounting opening in mm: 19.30 x 14.80. Suitable for GE2 / UDHome2 installation unit without floor covering recess.



## CE

A2 Stainless steel

#### Master data

| Item number         | 7407848                     |
|---------------------|-----------------------------|
| Туре                | MTGE2 2C                    |
| Description 1       | Mounting plate              |
| Description 2       | with 2x hole pattern Type C |
| Manufacturer        | OBO                         |
| Dimension           | 116x36x34                   |
| Material            | Stainless steel             |
| Smallest sales unit | 1                           |
| Unit of quantity    | Piece                       |
| Weight              | 4.7 kg                      |
| Weight unit         | kg/100 pc.                  |

# Technical data sheet

Mounting support, 2 x type C

## Item number: 7407848



# Dimensions Length 116 mm 91 116

#### **Technical data**

| Number of installable devices                     | 2             |
|---|---------------|
| Number of strain reliefs                          | 0             |
| Version for                                       | Support shape |
| Fastening type                                    | Lockable      |
| Labelling panel                                   | no            |
| Floor covering protection frame                   | no            |
| Floor plate                                       | no            |
| Lowerable to be flush-floor                       | no            |
| Seal installation option                          | no            |
| Installation opening for on-floor tank            | no            |
| Decouplable                                       | no            |
| Suitable for raised floor installation            | yes           |
| Suitable for screed-flush closed underfloor ducts | yes           |
| Suitable for screed-covered un-<br>derfloor ducts | yes           |
| Suitable for cavity floor installation            | yes           |
| Suitable for underfloor ducts                     | yes           |
| With floor covering recess                        | no            |
| Heavy-duty version                                | no            |
| Depth   | 36 mm         |
| Strain relief option                              | yes           |
|   |               |