Technical data sheet

90° bend 60 FT

Item number: 6036598



90° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



CER

St

Steel



Hot-dip galvanised

Master data

6036598
RB 90 640 FT
90° bend
for cable tray, horizontal
OBO
60x400
Steel
Hot-dip galvanised
DIN EN ISO 1461
1
Piece
251.3 kg
kg/100 pc.

Technical data sheet

90° bend 60 FT

Item number: 6036598



Width	400 mm
Height	60 mm
Plate thickness	0.8 mm
Dimension B	400 mm
Dimension R	50 mm
	•

Technical data

Bend (angle)	90°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	yes
Material thickness, floor plate	1 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	14 St.
Rail thickness	1.25 mm