

Technical data sheet

US 3 support FT

Item number: 6342372



Suspended support (U profile) of dimensions 50 x 30 mm with welded head plate.

For fastening to horizontal concrete ceilings and steel girders. For bracket widths of 400 mm or more, or if the bracket is mounted at the end of a suspended support, we recommend the use of the spacer, type DSK 25.



St Steel

FT Hot-dip galvanised

Master data

Item number	6342372
Type	US 3 K 120 FT
Description 1	Support
Description 2	with welded head plate
Manufacturer	OBO
Dimension	50x30x1200
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	189.9 kg
Weight unit	kg/100 pc.


Technical data sheet

US 3 support FT

Item number: 6342372




Dimensions



Length	1,200 mm
Length	3.93 ft
Width	50 mm
Height	30 mm
Plate thickness	0.08 in
Dimension L	1,200 mm

Loads



Chara



Max. total
= 10 cm
of ETA(a)

Technical data

Version for	U profile
Bracket length 200	2.1 kN
Bracket length 400	1.1 kN
Maintain electrical functions	yes
Material thickness	2 mm
Maximum tensile load	5 kN
With tothing	no